Application No. 10/585,902 Paper Dated: March 30, 2010

In Reply to USPTO Correspondence of September 30, 2009

Attorney Docket No. 0470-061793

AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the application.

Listing of Claims

1.-19. (Cancelled).

- 20. (Withdrawn) A packaging for pulverulent material comprising a container, a lid and a metering scoop, as well as an accommodation in the space delimited by the lid for accommodating said measuring scoop, wherein said lid is provided with an elevation oriented outwards when the lid is in the fitted position on said container, the interior of which elevation delimiting a cavity for at least partially accommodating said scoop and the inside of said lid being provided with fixing means for said scoop, said container having a seal for separating the contents of the container from the environment and extending over the free cross-sectional area of said container, said seal being spaced from the top of said container to accommodate part of said metering scoop, that the height of said accommodation in said lid is smaller than the height of said scoop such that when the lid is closed on said container the scoop can be received in the accommodation defined between said lid and said seal and in that said scoop is separate from said lid and container.
- 21. (Withdrawn) The packaging according to claim 20, wherein the highest point of said elevation extends at least 4 mm above the top peripheral edge of said packaging.
- 22. (Withdrawn) The packaging according to claim 20, wherein said lid is fixed, such that it can hinge, to a supporting edge, which is fixed to said container wall, wherein said lid and supporting edge comprise a single part of plastic material.
 - 23. (Withdrawn) The packaging according to claim 20, wherein said

Application No. 10/585,902 Paper Dated: March 30, 2010

In Reply to USPTO Correspondence of September 30, 2009

Attorney Docket No. 0470-061793

supporting edge is provided with a levelling-off surface.

- 24. (Withdrawn) The packaging according to claim 23, wherein said levelling-off surface is arranged close to a corner of said container.
- 25. (Withdrawn) The packaging according to claim 20, wherein said supporting edge is provided with a raised part, within which the lid is fitted horizontally, which raised part is provided with a cut-out, provided with a closure part that can be removed easily.
- 26. (Withdrawn) The packaging according to claim 20, wherein said scoop comprises a cup and wherein said fixing means are arranged to receive the scoop such that the open part of the cup is directed to said lid.
- 27. (Withdrawn) The packaging according to claim 20, wherein the container wall contains a heat-scalable material on the inside and wherein said scal comprises a plastic film scal, which scal is fixed to said container wall by heat scaling.
- 28. (Withdrawn) The packaging according to claim 20, wherein said container and said lid are essentially rectangular.
- 29. (Withdrawn) The packaging according to claim 27, wherein the distance (r) between the top of said film and the lowest point of the accommodation in the lid for the scoop is between 35 and 50 mm.
- 30. (Withdrawn) The packaging according to claim 20, wherein said container wall consists of a paper/metal foil/plastic laminate.
- 31. (Withdrawn) The packaging according to claim 20, wherein said wall of the container extends downwards beyond the base of said container to delimit an upright

Application No. 10/585,902 Paper Dated: March 30, 2010

In Reply to USPTO Correspondence of September 30, 2009

Attorney Docket No. 0470-061793

rim.

32. (Withdrawn) The packaging according to claim 20, wherein said lid has a circumferential edge and the top of said container has a peripheral edge, wherein in the closed position of said lid, said circumferential edge of said lid is inaccessibly accommodated within said peripheral edge, means being provided to interrupt said peripheral edge for access to said circumferential edge.

33. (Withdrawn) The packaging according to claim 32, wherein said means to interrupt said peripheral edge comprise a breakable peripheral edge portion.

34. (Withdrawn) The packaging according to claim 32, wherein said lid comprises a lip being locked in position by said means.

35. - 38. Cancelled.

39. (Withdrawn) The packaging according to claim 20, wherein the pulverulent material is baby food.

40. (Currently Amended) A method for providing a packaging filled with powder, such as baby food, comprising the provision of a container provided with a base and a top which has a peripheral edge, the inside wall of the container consisting of a heat-sealable material, filling powder into said container, placing a heat-sealable film above the powder and joining said film to said inside wall of the container 20-50 mm below the peripheral edge, provision being made for the fitting of a lid,

said packaging further comprising a scoop for dosing said powder, accommodated by the top part of the container, wherein said method further comprises the step of placing the scoop on the heat-sealable film,

Attorney Docket No. 0470-061793

said method further comprising the step of providing a lid provided with fixing means for said scoop, said lid fixed, such that it can hinge to a lid rim, said lid and lid rim provided from a single part of plastic material, and

said method further comprising the step of adhering said lid rim onto the peripheral top edge of said container, for defining an accommodation space between said lid and said heat-sealable film for said scoop.

41. - 43. (Cancelled).

- 44. (Previously Presented) The method according to claim 40, wherein the provision of a container comprises using blanks of wall material and base material as the starting materials and joining these together immediately before filling with product.
- 45. (Previously Presented) The method according to claim 40, wherein said heat-sealable film provides a gastight seal.
- 46. (Previously Presented) The method according to claim 40, where inert gas is fed into the space located below the film before/when sealing the film to the container wall.
- 47. (Previously Presented) The method according to claim 46, wherein gas is fed to a number of packs simultaneously.
- 48. (New) The method according to claim 40, wherein said heat-sealable film is provided less than 10 mm above said powder.